

PAT-NO: JP361285785A
DOCUMENT-IDENTIFIER: JP 61285785 A
TITLE: EXCIMER LASER DEVICE
PUBN-DATE: December 16, 1986

INVENTOR-INFORMATION:

NAME

HARUTA, TAKEO
WAKATA, HITOSHI
SATO, YUKIO
NAGAI, HARUHIKO

ASSIGNEE-INFORMATION:

NAME

MITSUBISHI ELECTRIC CORP

COUNTRY

N/A

APPL-NO: JP60127453

APPL-DATE: June 12, 1985

INT-CL (IPC): H01S003/22

US-CL-CURRENT: 372/57

ABSTRACT:

PURPOSE: To obtain a laser device, in which decrease in laser output is very small with respect to the oscillating frequency of laser pulses and a laser medium is sealed stably for a long period, by providing a means, which projects light so as to dissociate chemical bonding of hydrogen chloride and minute amount of impurities, which are included in the laser medium.

35 USC
119(b)

CONSTITUTION: Light having a wavelength in the range of 280nm~500nm is projected to a laser medium. Hydrogen chloride is used as one of the laser medium in an XeCl laser. Of molecular species, which are considered to be present in the cabinet of the laser, especially essential molecular species and the wavelengths of light, which are required to cut the molecular bonding, are shown in the Figure. When the light in the wavelength region less than 500nm is projected, most of chloride impurities, which are not required in laser oscillation, are dissociated. More desirably, when the wavelengths in the range more than 280nm and less than 500nm are used, the hydrogen chloride (HCl), which contributes to the laser oscillation is not dissociated, and only the chloride impurities can be dissociated.

COPYRIGHT: (C)1986,JPO&Japio